



As the name implies, Tandem brings two layers together in perfect sync—delivering both comfort and performance in one cohesive system. With a 2.5mm EPDM top layer and a 3mm, 5mm or 9mm rubber underlayment, Tandem is field-applied for a seamless 5.5mm, 7.5mm or 11.5mm flooring solution.

Tandem Standard Formats:

4' wide x 25' long rolls (double layer installation, 2.5mm top layer over 3mm, 5mm or 9mm underlayment = 5.5mm, 7.5mm or 11.5mm total thickness) and 2' x 2' x 1" Tandem XL tiles (minimums will apply)



The Tandem XL tile option takes things further with a 1" thickness and a floating block system for fast installs and next-level impact absorption. Tandem XL provides superior durability, comfort and force reduction with an attractive visual. The Tandem XL tile installation is simplified by using the XL Block System, requiring minimal adhesive and allowing the tiles to float. Tandem XL is ideal for a variety of commercial spaces where a durable, flexible and sustainable product is desired.

Designed to move with the rhythm of high-traffic spaces, it thrives in environments like hotel and multi-family fitness centers, workplace gyms, wellness rooms, therapy studios, yoga zones and more. Available in a range of colors and neutrals—Tandem is PVC FREE, Declare Label Red List Free, FloorScore certified and listed on mindful MATERIALS.



Declare.


SCS Certified



Dust



Pebble
TM001




Crosswalk
TM002




Asphalt
TM003



Echo
TM004



Gravel
TM005




Pavement
TM006




Burl
TM007




Dust
TM101




Slab
TM102




Orbit
TM103




Soil
TM104




Flare
TM105



Abyss
TM106



Grove
TM107



Wine
TM108

USA made, Tandem provides excellent sound reduction, comfort underfoot and resilience against heavy rolling loads. With no finish required, Tandem simplifies maintenance and offers a worry-free flooring solution. It can be maintained with the same easy-care methods used for other Capri products without polyurethane coatings.

